


# Regent 1500



**105  
Emmet**



**180  
Longreach**



**300  
Broken Hill**



**350  
Cobar**



**380  
Birdsville**



**545  
Georgetown**



**550  
Melrose**



**555  
Charleville**



**560  
Burke**



**700  
Silverton**



**740  
Winton**



**790  
Stamford**

# Regent 1500

Durable, easy to maintain and water resistant<sup>^</sup>, Regent vinyl planks are the perfect choice for creating a beautiful timber look throughout all areas of your home. The stunning colour palette provides a range of options to suit a variety of interiors, so you can find a warm and comfortable timber-look floor that complements your style. Available in two sizes, choose from the larger format Regent 1500 which features a longer and thicker plank, or Regent 1200 provides a smaller plank option.

Direct stick vinyl plank for a professional looking installation

## Technical Data

<b>Type:</b>	Vinyl Plank Flooring	<b>Colours:</b>	12
<b>Dimensions:</b>	1524mm x 178mm	<b>Country of Origin:</b>	South Korea
<b>Total Product Thickness:</b>	4.5mm	<b>Finish:</b>	Matte
<b>Wear Layer:</b>	0.5mm	<b>Surface:</b>	Embossed
<b>Units Per Box:</b>	10 boards	<b>Profile:</b>	Square Edge
<b>m<sup>2</sup> per box:</b>	2.71	<b>Coating System:</b>	PUR
<b>m<sup>2</sup> per pallet:</b>	162.6	<b>Installation Method:</b>	Direct Stick

## Performance

<b>Dimensional Stability:</b>	(ISO 23999) Length: 0.00%, Width: 0.00%, Curling 0.5%	<b>Light Reflectance Values:</b>	105 - 42.44   180 - 11.05   300 - 22.14   350 - 13.58   380 - 13.05   545 - 19.96   550 - 14.12   555 - 16.23   560 - 19.50   700 - 39.08   740 - 25.84   790 - 13.49
<b>Thermal Conductivity:</b>	TBA	<b>Flammability:</b>	(EN ISO 9239) CRF 7.2kW/m2
<b>Abrasion Rating:</b>	(EN 660-2) Group T	<b>Smoke Value:</b>	Direct Stick: (EN ISO 9239) 196% minutes   With Underlay: (EN ISO 9239) 167% minutes
<b>Impact Sound Reduction:</b>	Please refer to Godfrey Hirst Acoustic Performance specification sheet	<b>Slip Resistance:</b>	(AS/NZ 4586-2013) P2, R9
<b>Light Fastness:</b>	(EN ISO 105-B02) 6-7	<b>Warranty:</b>	25 Year Vinyl Plank Limited Residential Warranty*

## Sustainability

<b>Product Transparency:</b>	Global Green Tag, GreenRate Level A certified, Best Environmental Practice PVC certified product
<b>Accreditation:</b>	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.
<b>Indoor Air Quality:</b>	Green Building Council Compliant for VOC emission rate limits



# Regent 1500



Mid Range



Colour Variation



Best  
Environmental  
Practice PVC